



2170894	DATA SHEET	
valid from: 13.11.2020	ETHERLINE® FD P FC Cat. 5 2x2x22/7 AWG	

Application

Field of use:	Connecting cable for generic cabling systems acc. to ISO/IEC 11801 and EN 50173
Performance:	Bandwidth up to 100 MHz acc. to IEC 61156-6 Category 5e and EN 50288-2-2
Characteristics:	halogen free, flame retardant and largely resistant to acids, alkalis and certain oils, the "Fast Connect" design allows easy stripping and assembly of the cable
Applications:	PROFINET, EtherCAT, EtherNet/IP, Power over Ethernet (IEEE 802.3af), Power over Ethernet Plus (IEEE 802.3at) and many others




Design

Certification	c(UL)us CMX 75°C acc. to UL 444 & CSA 22.2 No. 214
Conductor	stranded tinned copper 22/7 AWG
Insulation	polyolefin core Ø: ca. 1.5 mm
Core identification code	pair 1: white/blue, pair 2: yellow/orange
Stranding	star quad
Inner sheath	FRNC outer Ø: ca. 3.9 mm
Screen	special aluminium foil (overlapping) on top: braid of tinned copper wires (coverage 85 % ± 5 %)
Outer sheath	PUR green, similar RAL 6018 outer Ø: 6.5 mm (± 0.3 mm)

Electrical properties at 20°C

Loop resistance	max. 11.48 Ω/100 m
Insulation resistance	min. 5 GΩ xkm
Mutual capacitance	nom. 52 nF/km
Characteristic impedance	nom. 100 Ω acc. to IEC 61156-6
Velocity of propagation	0,67c
Signal propagation time	<520 ns/100 m
Delay skew	≤ 25 ns/100 m
Operating voltage (max.)	EN: 100 V (not for power purposes)
Rated voltage	UL: 300 V
Test voltage	core/core: 2000 V core/screen: 2000 V

Creator: KIOS / PDC	Document: DB2170894EN	Page 1 of 2
Released: ALTE / PDC	Version: 09	

2170894	DATA SHEET	
valid from: 13.11.2020	ETHERLINE® FD P FC Cat. 5 2x2x22/7 AWG	

Electrical transmission properties at 20°C

The transmission characteristics meet the requirements of the standards EN 50288-2-2 and IEC 61156-6 for category 5e. The normative requirements for the transmission properties are shown in the following table:

f [MHz]		4	10	16	20	31,25	62,5	100
(max.) Attenuation	[dB/100 m]	6	9,5	12,1	13,5	17,1	24,8	32
(min.) TCL	[dB]	34	30	28	27	25,1	22	20
(min.) EL TCTL	[dB/100 m]	23	15	10,9	9	5,1	—	—
(min.) NEXT	[dB]	56,3	50,3	47,2	45,8	42,9	38,4	35,3
(min.) PS EL FEXT	[dB/100 m]	49	41	36,9	35	31,1	25,1	21
(min.) ACR-F/EL FEXT	[dB/100 m]	52	44	39,9	38	34,1	28,1	24
(min.) Return Loss	[dB]	23	25	25	25	23,6	21,5	20,1

Mechanical and thermal properties

Minimum bending radius	fixed: 6x cable diameter continuous flexing: 8x cable diameter
Temperature range	fixed: -30 °C up to +80 °C continuous flexing: -20 °C up to +60 °C UL: 75 °C
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 VW-1 acc. to UL 1581 §1080
Halogen free	acc. to VDE 0472-815
Oil resistance	acc. to EN 50363-10-2
General requirements	This cable is conform to EU-Directive 2014/35/EU (Low Voltage Directive) and to EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: KIOS / PDC	Document: DB2170894EN	Page 2 of 2
Released: ALTE / PDC	Version: 09	