

# ZMVV.E205350 - Wire Connectors and Soldering Lugs

Note: We are enhancing our systems and you may notice missing/outdated data. During this interim period, please refer to your Certificate of Compliance or contact our Customer Service at <https://www.ul.com/about/locations>.

## Wire Connectors and Soldering Lugs

### ELPRESS AB

E205350

Industrivaegen 15  
Kramfors, SE-872 32 Sweden

Trademark and/or Tradename:  ,  , 

Note: For additional marking information, refer to the [Guide Information Page](#).

**Butt splices connectors**, Model(s): KS(1,0), KS(1,5), KS(2,5), KS10, KS4, KS6, KSF120, KSF150, KSF16, KSF185, KSF240A, KSF25, KSF300A, KSF35, KSF400A, KSF50, KSF500, KSF70, KSF95

**Splicing wire connectors**, Model(s): KST10+, KST120+, KST150+, KST16+, KST185+, KST240+, KST25+, KST300+, KST35+, KST400+, KST50+, KST500+, KST70+, KST95+

**Splicing wire connectors, "Non-insulated crimp type wire connectors Series"**, Model(s): KSF followed by 95, 120, 150, 185, 240A, 300A may be followed by NS, BL, ZN, AG or NI.

**Terminal connectors**, Model(s): KA1525SK, KA1532G, KA1532R, KA1537G, KA1537R, KA1543G, KA1543R, KA1553G, KA1553R, KA1565G, KA1565R, KA2527SK, KA2532G, KA2532R, KA2537G, KA2537R, KA2543G, KA2543R, KA2553G, KA2553R, KA2565G, KA2565R, KA2585R, KA4610R, KA4643G, KA4643R, KA4652SK, KA4653G, KA4653R, KA4665G, KA4665R, KA4685G, KA4685R

**Terminal connectors**, Model(s): KR, followed by (1,0), (1,5), (2,5), 4, 6, 10, may be followed by 3, 4, 5, 6, 8, 10, 12.

**Terminal connectors**, Model(s): KRF, followed by 16, 25, 35, 50, 70, 95, 120, 150, 185, 240A, 300A, 400A, 500, may be followed by 00, 5, 6, 8, 10, 12, 16, 20, 24, followed by a 1 or 2-digit number with or without x2, and by a 2-digit number -15 through -45, with or without a two-digit number between 45 and 90

**Terminal connectors**, Model(s): KRF, followed by 35, 50, 70, 95, 120, 150, 185, 240A or 300A followed by suffix 6, 8, 10, 12, 16, 20, 24, 10X2, 12X2 or 16X2 may be followed by 45GR or 90GR followed by SP.

**Terminal connectors**, Model(s): KRT, followed by 10, 16, 25, 35, 50, 70, 95 or 120, may be followed by NS, followed by a 1 or 2-digit number, and by suffix -45GR, -90GR or 90x90GR+

**Terminal connectors**, Model(s): KRT, followed by 10, 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400, or 500, followed by a 1 or 2-digit number+

**Terminal connectors**, Model(s): KRT, followed by 10, 16, 25, 35, 50, 70, 95, or 120, may be followed by NS, followed by a 1 or 2-digit number, and by -45GR, or -90GR+

**Terminal Connectors, "Non-insulated crimp type wire connectors Series",** Model(s): KRF followed by 95, 120, 150, 185, 240A, 300A may be followed by 00, or by 1 or 2-digit numbers, followed by a 1 or 2-digit number with or without x2 may be followed by, NS, BL, ZN, AG or NI, may be followed by an N and 1 or 2-digit number or a C or a D and by 2-digit number -15 through -45, with or without two-digit number between 45 and 90, may be followed by an SP and 1 or 2-digit, may be followed by, NS and/or BL, ZN, AG or NI.

**Terminal Connectors, "Non-insulated crimp type wire connectors Series",** Model(s): KRFN followed by 95, 120, 150, 185, 240A, 300A may be followed by 00, or by 1 or 2-digit numbers, followed by a 1 or 2-digit number with or without x2 may be followed by, NS, BL, ZN, AG or NI, may be followed by an N and 1 or 2-digit number or a C or a D and by 2-digit number -15 through -45, with or without two-digit number between 45 and 90, may be followed by an SP and 1 or 2-digit, may be followed by, NS and/or BL, ZN, AG or NI.

**Terminal Connectors, "Non-insulated crimp type wire connectors Series",** Model(s): KRFS followed by 95, 120, 150, 185, 240A, 300A, followed by 00, 5, 6, 8, 10, 12, 16 may be followed by NS and/or BL, ZN, AG or NI.

\* - May be packaged in big, medium or small plastic bags.

+ - May be followed by suffix -UL.

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:  
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

# ZMVV7.E205350 - Wire Connectors and Soldering Lugs Certified for Canada

Note: We are enhancing our systems and you may notice missing/outdated data. During this interim period, please refer to your Certificate of Compliance or contact our Customer Service at <https://www.ul.com/about/locations>.

## Wire Connectors and Soldering Lugs Certified for Canada

### ELPRESS AB

E205350

Industrivaegen 15  
Kramfors, SE-872 32 Sweden

Trademark and/or Tradename:



Note: For additional marking information, refer to the [Guide Information Page](#).

**Butt splices connectors**, Model(s): KS(1,0), KS(1,5), KS(2,5), KS10, KS4, KS6, KSF120, KSF150, KSF16, KSF185, KSF240A, KSF25, KSF300A, KSF35, KSF400A, KSF50, KSF500, KSF70, KSF95

**Splicing wire connectors, "Non-insulated crimp type wire connectors Series"**, Model(s): KSF followed by 95, 120, 150, 185, 240A, 300A may be followed by NS, BL, ZN, AG or NI.

**Terminal connectors**, Model(s): KA1525SK, KA1532G, KA1532R, KA1537G, KA1537R, KA1543G, KA1543R, KA1553G, KA1553R, KA1565G, KA1565R, KA2527SK, KA2532G, KA2532R, KA2537G, KA2537R, KA2543G, KA2543R, KA2553G, KA2553R, KA2565G, KA2565R, KA2585R, KA4610R, KA4643G, KA4643R, KA4652SK, KA4653G, KA4653R, KA4665G, KA4665R, KA4685G, KA4685R

**Terminal connectors**, Model(s): KR, followed by (1,0), (1,5), (2,5), 4, 6, 10, may be followed by 3, 4, 5, 6, 8, 10, 12.

**Terminal connectors**, Model(s): KRF, followed by 16, 25, 35, 50, 70, 95, 120, 150, 185, 240A, 300A, 400A, 500, may be followed by 00, 5, 6, 8, 10, 12, 16, 20, 24, followed by a 1 or 2-digit number with or without x2, and by a 2-digit number -15 through -45, with or without a two-digit number between 45 and 90

**Terminal connectors**, Model(s): KRF, followed by 35, 50, 70, 95, 120, 150, 185, 240A or 300A followed by suffix 6, 8, 10, 12, 16, 20, 24, 10X2, 12X2 or 16X2 may be followed by 45GR or 90GR followed by SP.

**Terminal connectors**, Model(s): KRT, followed by 10, 16, 25, 35, 50, 70, 95, or 120, may be followed by NS, followed by a 1 or 2-digit number, and by -45GR, or -90GR+

**Terminal Connectors, "Non-insulated crimp type wire connectors Series"**, Model(s): KRF followed by 95, 120, 150, 185, 240A, 300A may be followed by 00, or by 1 or 2-digit numbers, followed by a 1 or 2-digit number with or without x2 may be followed by, NS, BL, ZN, AG or NI, may be followed by an N and 1 or 2-digit number or a C or a D and by 2-digit number -15 through -45, with or without two-digit number between 45 and 90, may be followed by an SP and 1 or 2-digit, may be followed by, NS and/or BL, ZN, AG or NI.

**Terminal Connectors, "Non-insulated crimp type wire connectors Series",** Model(s): KRFN followed by 95, 120, 150, 185, 240A, 300A may be followed by 00, or by 1 or 2-digit numbers, followed by a 1 or 2-digit number with or without x2 may be followed by, NS, BL, ZN, AG or NI, may be followed by an N and 1 or 2-digit number or a C or a D and by 2-digit number -15 through -45, with or without two-digit number between 45 and 90, may be followed by an SP and 1 or 2-digit, may be followed by, NS and/or BL, ZN, AG or NI.

**Terminal Connectors, "Non-insulated crimp type wire connectors Series",** Model(s): KRFS followed by 95, 120, 150, 185, 240A, 300A, followed by 00, 5, 6, 8, 10, 12, 16 may be followed by NS and/or BL, ZN, AG or NI.

\* - May be packaged in big, medium or small plastic bags.

+ - May be followed by suffix -UL.

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:  
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"

# ZMVV2.E205350 - Wire Connectors and Soldering Lugs - Component

*Note: We are enhancing our systems and you may notice missing/outdated data. During this interim period, please refer to your Certificate of Compliance or contact our Customer Service at <https://www.ul.com/about/locations>.*

## Wire Connectors and Soldering Lugs - Component

**ELPRESS AB**

Industrivaegen 15  
Kramfors, SE-872 32 Sweden

E205350

Marking: Company name and model designation.

Note: For additional marking information, refer to the [Guide Information Page](#).

**Pressure terminal connectors**, Model(s): AS120, AS120H

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions:  
1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"