Valid from: 17.09.2018

EPIC<sup>®</sup> SIGNAL M23 17 E/P SOLDERING



## Description

- Inserts for M23 circular connectors
- Inserts with solder pins at the connection side for soldering in PCB boards.
- Ideal in combination with M23 housings of type B1/B2 for rear wall-mounting.



### **General characteristics**

Series	SIGNAL M23
Version	E-part = rotation to the right (clockwise) /
	P-part = rotation to the left (anticlockwise)
Number of contacts	17
	Solder termination; solder pins with Ø 1.0 mm for
Termination method	PCB soldering.
	Pin length from rear edge of housing B1/B2: 4 mm
Temperature range	-25 to +125 °C
Contacts included	ја

### Product variations

Article no.	Version	Contacts
44420160	P-Part	male contacts, PCB solder
44420161	P-Part	female contacts, PCB solder
44420162	E-Part	male contacts, PCB solder
44420163	E-Part	female contacts, PCB solder

#### Mechanical characteristics

Cycles of mechanical operation	100	
Electrical characteristics		
Rated voltage Rated impulse voltage Rated current Contact resistance Pollution degree	50 V 0,8 kV 7 A < 4 mOhm 3	
Materials and surfaces		
Materials and surfaces Insert Contacts, base material Contacts, surface	PA brass Au	
Insert Contacts, base material	brass	

Creator: MANA2/PDP	Document: DB44420160EN	Dage 1 of 2
Released: IVSE1/PDP	Version: 02	Page 1 of 3
We reserve all rights according to DIN ISO 16016		

# **DATA SHEET**


Valid from: 17.09.2018

EPIC<sup>®</sup> SIGNAL M23 17 E/P SOLDERING





### Drawings











Released: IVSE1/PDP Version: 02	Creator: MANA2/PDP	Document: DB44420160EN	Page 2 of 3
	Released: IVSE1/PDP	Version: 02	

Valid from: 17.09.2018

EPIC<sup>®</sup> SIGNAL M23 17 E/P SOLDERING





Good chemical resistance

∎∎

Industrial machinery and plant engineering



Mechanical resistance



Assembly time



Robust

Wind Energy



Variety of approval certifications

**Info** With solder pins for PCB boards Only for housing type A1, B1, B2

### Application range

Plant engineering Measurement and control technology Apparatus construction

### Remark

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise) Photographs are not to scale and do not represent detailed images of the respective products.

Creator: MANA2/PDP	Document: DB44420160EN	Daga 2 of 2
Released: IVSE1/PDP	Version: 02	Page 3 of 3
We recerve all rights apporting to DIN ISO 16016		